

DinkMar Big Six Leaf Master Standard Features

Pricing for Leaf Vacuum Machine

DINKMAR offers these standard features:

- **Engine**
 - 4045T 85hp John Deere or 3800T 96hp Kubota Motor
 - Temperature Gauge, Oil Pressure Gauge, Volt Meter, Hour Meter, Tachometer, Governor, and Hand Throttle
 - High Temperature and Low Oil Pressure Automatic Shut Down
 - 12 Volt Electrical System
 - 40 Amp Alternator
 - 40 Gallon Fuel Tank
 - Heavy Duty Battery

- **Blower Housing**
 - Replaceable Blower Housing
 - #7 & #10 Thick Steel
 - ¼" Thick Steel One Piece Replaceable Liner
 - Blower is Rated at 22,000 C.F.M.

- **Impeller**
 - 30" Diameter
 - 3/8" AR-400F Material (Brinell Hardness Exceeding 400)
 - 6 Blades and 2 Gussets per Blade
 - Impeller is Statically and Dynamically Balanced

- **Intake Hose and Arm**
 - 16" Diameter x 120" Long Intake Hose
 - Wire Reinforced Hose

- **Trailer Lighting**
 - LED Lighting– Park, Stop, and Turn
 - LED Marker Lighting

- **Machine Will Be Primed and Painted**
 - Standard Color is Yellow or White

- **Engine**
 - Standard Features
 - 11" Twin Disc or 13" Automotive Clutch
 - Gear Driven Hydraulic Pump
 - Steel Belt Guard (Opens for Easy Maintenance)
 - Common Back Belt Absorbs Shock to Clutch

- **Blower Housing**
 - Standard Features
 - Rotated 45 Degree Exhaust

- **Impeller**
 - Standard Features

- **Intake Hose and Arm**

- Standard Features
 - Joystick Controls Vertical & Horizontal Movement of Intake Nozzle
 - 3rd Axis on the In-take Nozzle and Swing Arm Assembly
 - Seat for Operator With/With out Seat Belt
 - 16' Intake Nozzle Located on Curb-side of the Machine
 - Special Rubber Tire In-take Nozzle Assembly
 - Reach of 10' 6" from the Machine to End of Intake Nozzle
- **Exhaust Tube**
 - Stationary Steel Elbow Square to 16" Round at 45 Degree
 - 4' x 16" Rubber Exhaust Tube
- **Trailer**
 - Single Axle (6,000 Pounds)
 - 8 Ply x 15" Tires
 - 136" length, 101" wide, and 116" height
 - Rectangular Trailer Frame with 3 1/2" Square Telescoping Draw Bar and Adjustable Hitch Height
 - Bottom of Exhaust Tube at Level Position is 92" to 98" from Ground Up
 - Exhaust Tube Extends 12" or more Past Center of Pintle Hitch
 - Power Parking Jack w/Swivel Jack Wheel
1. **Factory Set-up** can be arranged for an additional **\$250.00 to \$2,000.00** The factory setup includes a factory representative walking the customer through the machine and spending part of the day with the customer operating the machine.
 2. **Note On Factory Set-up**
Only good for the month of January to September