

# DinkMar Leaf Master A-Frame Standard Features

## Pricing for Leaf Vacuum Machine

### DINKMAR offers these standard features:

- **Engine**
  - 3800T 96hp Kubota or 4045T 85hp John Deere Motor
  - Temperature Gauge, Oil Pressure Gauge, Volt Meter, Hour Meter, Tachometer, Governor, and Hand Throttle
  - High Temperature and Low Oil Pressure Automatic Shut Down
  - 12 Volt Electrical System
  - 40 Amp Alternator
  - 40 Gallon Fuel Tank
  - Heavy Duty Battery
  - Manual Throttle System
- **Blower Housing**
  - Replaceable Blower Housing
  - #7 & #10 Thick Steel
  - ¼" Thick Steel One Piece Replaceable Liner
  - Blower is Rated at 22,000 C.F.M.
- **Impeller**
  - 30"/32" Diameter Fan
  - 3/8" AR-400F Material (Brinell Hardness Exceeding 400)
  - 6 Blades and 2 Gussets per Blade
  - Impeller is Statically and Dynamically Balanced
- **Intake Hose and Arm**
  - 16" Diameter x 120" Long Intake Hose
  - Wire Reinforced Hose
- **Trailer Lighting**
  - LED Lighting– Park, Stop, and Turn
  - LED Marker Lighting
- **Machine Will Be Primed and Painted**
  - Standard Color is Yellow or White
- **Engine**
  - Standard Features
  - 11" Twin Disc or 13" Automotive Clutch Assembly
  - Gear Driven Hydraulic Pump
  - Steel Belt Guard (Opens for Easy Maintenance)
  - Common Back Belt Absorbs Shock to Clutch
- **Blower Housing**
  - Standard Features
  - Oscillating 360° Turntable Base Assembly with Elbow
  - Hydraulic Power Lifting and Float System

- **Impeller**
  - Standard Features
  
- **Intake Hose and Arm**
  - Standard Features
  - Joystick Controls Vertical & Horizontal Movement of Intake Nozzle
  - 3<sup>rd</sup> Axis on the In-Take Nozzle and Swing Arm Assembly
  - Seat for Operator With/With out Seat Belt
  - 16' Intake Nozzle Located on Curb-side of the Machine
  - Special Rubber Tire Intake Nozzle Assembly
  - Reach of 10' 6" from the Machine to End of Intake Nozzle
  
- **Exhaust Tube**
  - Inside Liner is Assembled of 1/4" Material Plus for Longer Life
  - Most of DinkMar Machine has lasted for an Average of 8Years before any Repair
  - Power Cylinder Height Adjustment for Exhaust Tube Elbow
  - This keep the employee on the ground and safe
  - 12 Ga. Steel Exhaust Tube for Longer Life than 3' or 4' Rubber Exhaust Tube
  
- **Trailer**
  - Single Axle (6,000 Pounds)
  - 8 Ply x 15" Tires
  - 136" length, 101" wide, and 116" height
  - Rectangular Trailer Frame with 3 1/2" Square Telescoping Draw Bar and Adjustable Hitch Height
  - Bottom of Exhaust Tube at Level Position is 102" from Ground
  - Exhaust Tube Extends 12" to 18" Past Center of Pintle Hitch
  - Power Parking Jack with Steel Swivel Wheel
  
- 1 Factory Set-up** can be arranged for an additional **\$250.00 to \$2000.00** for factory setup includes a factory representative walking the customer through the machine and spending part of the day with the customer operating the machine.
- 2 Note On Factory Set-up**  
**Only good for the month of January to September**